# Connection unit for multiple wall-mounted printed circuit boards

## 550-14090

This connection unit forms the connection between the installation and multiple wall-mounted circuit boards. This unit can be mounted anywhere. To mount the connection unit, use the special set of claws.

**Technical data**

Connection unit for multiple wall-mounted printed circuit boards
Connection unit for multiple wall-mounted printed circuit board
A wall-mounted printed circuit board includes all the electrical and mechanical components required to connect one or several push buttons to the Niko Home Control installation. Niko offers horizontal, vertical, single or multiple printed circuit boards. Choose the type of printed circuit board depending on the number of action buttons required and on a horizontal or vertical assembly. The printed circuit board can be easily replaced by a larger one at a later stage if the need arises to expand the installation.
You need one connection unit for each multiple wall-mounted printed circuit board you wish to connect. Connection units are available separately. The connection unit includes a double plug-in connector, which allows you to connect the bus cable and establish a connection to the next control element. The connector has two contacts with two openings each.

Technical data:
• wall-mounted printed circuit board material: epoxy
• material thickness: 1 mm
• one double connector

Use a set of claws if no screw holes are provided in the flush-mounting box. Sets of claws for single and multiple wall-mounted printed circuit boards are available separately.
• Function: A wall-mounted printed circuit board includes all the electrical and mechanical components required to connect one or several push buttons to the Niko Home Control installation. Niko offers horizontal, vertical, single or multiple printed circuit boards. Choose the type of printed circuit board depending on the number of control buttons required and on a horizontal or vertical assembly. The printed circuit board can be easily replaced by a larger one at a later stage if the need arises to expand the installation. You need one connection unit for each multiple wall-mounted printed circuit board you wish to connect. Connection units are available separately. The connection unit includes a double plug-in connector, The connection unit includes a double plug-in connector, which allows you to connect the bus cable and establish a connection to the next control element. The connector has two contacts with two openings each.
• Wire connection
  – double plug-in connector
• Wire capacity
  – 2 x 0.5 to 1 mm² wire per terminal
• Fixing method
  – to mount the connection unit, use the set of claws 450-00068.

niko

• Dimensions (HxWxD): 50.7 x 42.9 mm

• Marking: CE

$C \in$

niko